

PRODUCT FEATURES

Components	
Transducers	2x 18" diameter, 4" duo technology voice coil, Low power compression, high temperature neodymium magnets, Cone Driver
Enclosure materials	Baltic Birch plywood
Finish	Wear Resistant Textured Black Paint
Grille	Powder coated perforated steel with foam
Fittings	4 x 4" (100mm) castors, 16 x pocket handles 4 x slots for stacking with rubber sticks
Dimensions	
Height	1132 mm / 44,57 in
Width	700 mm / 27,56 in
Depth (without castors)	610 mm / 24,02 in
Depth (with castors)	740 mm / 29,13 in
Weight	???? kg / ???? Lbs

SYSTEM SPECIFICATIONS

Frequency Response	
±3dB	35 Hz - 110 Hz
Maximum output (dB SPL @ 1m) ¹	135
Coverage angle (degrees, @ -6dB points) ³	
Vertical	180
Horizontal	360
Connector	
Signal input	1x XLR female
Signal loop	1x XLR male
AC power input	1x Powercon
Input impedance	20Kohm (electronically balanced)
Input Sensitivity	+4dBu (1.23V) for full output power
Controls	
Level	∅ to 0dB
Input polarity switch	Input polarity invert
Power switch	On/off to AC power
Indicators	
Protect	1x LED
Ready	1x LED
Peak	1x LED
Input polarity	1x LED
Amplifier design	Class H (2 tier)
Amplifier output power	1 x 1200W (%0,5 THD @ 4ohm,80Hz sine)
Power Requirements	230VAC - 50Hz
Power Consumptions	
@ 1/8 full output power	1,9A

Servo Elektronik reserve the right to alter functions or the specification without prior notice.